

Cont  
A1

said containers being detachably attached to one another to form a combined collective container structure having a cylindrical exterior shape

4. A separable container apparatus as described in claim 2, wherein said first side wall of one said container is detachably attached to said second side wall of another said container.

A2  
Sub  
B1

5. A separable container apparatus as described in claim 2, wherein each of said containers includes an elongate first flange member securely attached to an exterior of said first side wall and extending along a length of said top edge thereof, and also includes a first recessed portion disposed in said first side wall and extending along a length of said bottom edge thereof, and further includes a first slot disposed in said first recessed portion and extending the length of said bottom edge.

Sub  
B2  
A3

7. A separable container apparatus as described in claim 2, wherein each of said containers further includes a second slot disposed in an exterior of said second wall and extending along a length of said top edge thereof and being adapted to receive said first flange member of another said container, and also includes an elongate second flange member being securely attached to an exterior of said second side wall and extending outwardly and along a length of said bottom edge thereof and being adapted to be received in said first recessed portion and said first slot of another said container.

Sub  
A4 B3

10. A separable container apparatus as described in claim 1, wherein said lids include a first lid which is adapted to detachably fasten to all of said containers being attached to one another, and

Cont  
also includes a second lid which is adapted to detachably fasten to two of said containers being attached to one another, and further includes a third lid which is adapted to detachably fasten to one of said containers.

A4 7 11. A separable container apparatus as described in claim 10, wherein said first lid is circular shaped and fastenable about top edges of said third side walls to close upon said open tops of said containers.

Sub B4 8 12. A separable container apparatus as described in claim 1, wherein each of said containers essentially represents 1/3 of said cylindrical structure.

13. A separable container apparatus as described in claim 1, wherein two of said containers are detachably attached to one another to essentially form 2/3 of said cylindrical structure with said second lid having a plurality of edges and being adapted to fasten about said top edges of said third side walls of the two of said containers and about said top edge of said first side wall of one of said containers and about said top edge of said second side wall of the other of said containers, said edges of said second lid including a curved first edge, a straight second edge, and a straight third edge which is angled more than 90 degrees and less than 180 degrees relative to said second edge thereof.

14. A separable container apparatus as described in claim 2, wherein said third lid has a plurality of edges and is adapted to fasten about said top edges of said first, second, and third side walls of one of said containers, said edges of said third lid including a curved first edge, a straight second edge, and a straight

Cont  
A4  
third edge which is angled more than 180 degrees and less than 270 degrees relative to said second edge thereof.

15. A separable container apparatus as described in claim 2, wherein said third side walls are essentially curved, and said first and second side walls are essentially planar.

**Please add the following claim(s):**

A5  
17. A separable container apparatus comprising:  
containers each having an open top, a bottom wall, and a peripheral side wall assembly securely attached to and extending upwardly from said bottom wall, said containers being detachably connected to one another to essentially form a single structure having a plurality of storage compartments, said peripheral side wall assembly of each said container including a first side wall, a second side wall, and a third side wall, each of said first and second side walls having a top edge and a bottom edge, said first and second side walls of one of said containers being detachably attached to said first and second side walls of the others of said containers, said first side wall of one said container being detachably attached to said second side wall of another said container, each of said containers including an elongate first flange member securely attached to an exterior of said first side wall and extending along a length of said top edge thereof, and also including a first recessed portion disposed in said first side wall and extending along a length of said bottom edge thereof, and further including a first slot disposed in said first recessed portion and extending the length of said bottom edge, each said elongate first flange member including a first portion extending outwardly generally perpendicular of a respective said first side wall, and also

Cont  
A5

including a second portion being integrally attached to said first portion and being angled relative to said first portion and being disposed downwardly, each of said containers further including a second slot disposed in an exterior of said second wall and extending along a length of said top edge thereof and being adapted to receive said first flange member of another said container, and also including an elongate second flange member being securely attached to an exterior of said second side wall and extending outwardly and along a length of said bottom edge thereof and being adapted to be received in said first recessed portion and said first slot of another said container, each of said second slots being essentially angled and having a first portion which extends into said second wall and also having a second portion which is angled relative to said first portion and which is continuous of said first portion and which is disposed downwardly, each said second flange member including a first portion extending outwardly generally perpendicular of a respective said second side wall, and also including a second portion being integrally attached to said first portion and being angled relative to said first portion and being disposed upwardly; and

lids being removably attached to any combination of attached said containers; said lids including a first lid which is adapted to detachably fastened to all of said containers being attached to one another, and also including a second lid which is adapted to detachably fasten to two of said containers being attached to one another, and further including a third lid which is adapted to detachably fasten to one of said containers, said containers being detachably attached to one another to essentially form a cylindrical structure having said multiple compartments therein with said first lid being circular shaped and fastenable about top edges of said third side walls to close upon said open tops of said containers.

each of said containers essentially representing a first portion of said cylindrical structure, two of said containers being detachably attached to one another to essentially form a second portion of said cylindrical structure with said second lid having a plurality of edges and being adapted to fasten about said top edges of said third side walls of the two of said containers and about said top edge of said first side wall of one of said containers and about said top edge of said second side wall of the other of said containers, said edges of said second lid including a curved first edge, a straight second edge, and a straight third edge, said third lid having a plurality of edges and being adapted to fasten about said top edges of said first, second, and third side walls of one of said containers, said edges of said third lid including a curved first edge, a straight second edge, and a straight third edge, said third side walls being essentially curved, and said first and second side walls being essentially planar, said lids further having lips extending outwardly from one or more of said edges for opening and removing said lids from said containers.